



## Datasheet for three-phase Squirrel-Cage-Motors

**Order Number: 1LE0101-0DB24-1AA4**

Client-order-no.:

Order-no.:

Offer-no.:

Remarks:

Item-no.:

Consignment-no.:

Project:

### Electrical data

Rated motor voltage:	525VD
Frequency:	50 Hz
Rated motor power:	0.55 kW
Rated motor speed:	1425 1/min
Maximum Speed:	3600 1/min
Number of poles:	4
No load current:	0.61 A
Rated current:	1.01 A
Starting current:	6
Rated motor torque:	3.69 Nm
Torque class:	F
Starting torque:	2
Breakdown torque:	2.7
Efficiency class:	-
Efficiency 100% Load:	74.0%
Efficiency 75% Load:	74.7%
Efficiency 50% Load:	70.1%
Power factor 100% Load:	0.8
Motor protection:	without
Terminal box position:	terminal box on top

### Mechanical data

Noise (Lpfa):	45.00 dB(A)
Moment of inertia:	0.0021 kg m <sup>2</sup>
Cantilever force for x0:	790 N
Cantilever force for xmax:	640 N
Bearing drive end:	6204 2Z C3
Bearing non-drive end (hor.mount.):	6204 2Z C3
Bearing non-drive end (vert.mount.):	6204 2Z C3
Drain holes:	no
Regreasing device:	no
Relubrication interval at 40°C:	
Coating:	RAL 7030 stone gray

### Site conditions

Ambient temperature:	-20.0°C to +40°C
Altitude above sea level:	1000m
Standards and specifications:	IEC

### General data

Frame size:	80M
Type of construction:	IMB3
Weight in kg (net):	17.5 kg
Frame material:	Cast iron
Fan cover material:	metal
Degree of protection:	IP 55
Method of cooling:	Self-ventilated (IC 411)
Vibration class:	A (standard)
Insulation:	155(F) / 130(B)
Duty type:	S1 = cont. operation
Direction of rotation:	bidirectional

### Terminal box

Material of terminal box	Cast iron
Terminal screw thread:	M4
Max. cable cross-sectional area:	1.5 mm <sup>2</sup>
Cable diameter from ... to ...:	13 - 18 mm
Cable entry:	M25 x 1.5 + M16 x 1.5
Cable gland:	no

### Explosion protection

Type of protection:	without (standard)
---------------------	--------------------

### Special configurations

Technical and ordering data are subject to change. There may be discrepancies between calculated and rating plate values.

Printed on 2013-04-15