

# SIEMENS

## Datasheet for three-phase Squirrel-Cage-Motors

Order Number: 1LE0103-3AA23-4AB4

Client-order-no.:

Order-no.:

Offer-no.:

Remarks:

### Electrical data

Rated motor voltage:	400VD / 690VY
Frequency:	50 Hz
Rated motor power:	132 kW
Rated motor speed:	2982 1/min
Maximum Speed:	3600 1/min
Number of poles:	2
No load current:	46.5 A
Rated current:	220 A
Starting current:	7.5
Rated motor torque:	423 Nm
Torque class:	J
Starting torque:	2.3
Breakdown torque:	2.9
Efficiency class:	IE 3
Efficiency 100% Load:	95.4%
Efficiency 75% Load:	95.3%
Efficiency 50% Load:	92.40%
Power factor 100% Load:	0.90
Motor protection:	3 PTC thermistors for tripping
Terminal box position:	terminal box on top

### Mechanical data

Noise (Lpfa):	78.00 dB(A)
Moment of inertia:	1.7 kg m <sup>2</sup>
Cantilever force for x0:	7100 N
Cantilever force for xmax:	6200 N
Bearing drive end:	6319 C3
Bearing non-drive end (hor.mount.):	6319 C3
Bearing non-drive end (vert.mount.):	7319 AC
Drain holes:	yes
Regreasing device:	yes
Relubrication interval at 40°C:	3000 h

Technical and ordering data are subject to change. There may be discrepancies between calculated and rating plate values.

Printed on 2013-02-08

Coating: RAL 7030 stone gray

### Site conditions

Ambient temperature: -20.0°C to +40°C

Altitude above sea level: 1000m

Standards and specifications: IEC



Item-no.:

Consignment-no.:

Project:

### General data

Frame size:	315M
Type of construction:	IMB3
Weight in kg (net):	900 kg
Frame material:	Cast iron
Fan cover material:	metal
Degree of protection:	IP 55
Method of cooling:	Self-ventilated (IC 411)
Vibration class:	A (standard)
Insulation:	155(F) / 130(B)
Duty type:	S1 = cont. operation
Direction of rotation:	bidirectional

### Terminal box

Material of terminal box:	Cast iron
Terminal screw thread:	M12
Max. cable cross-sectional area:	240 mm <sup>2</sup>
Cable diameter from ... to ...:	37 - 44 mm
Cable entry:	M63 x 1.5 + M63 x 1.5
Cable gland:	no

### Explosion protection

Type of protection: without (standard)

### Special configurations